

Trolley Fire Extinguisher 50Kg Dry Powder

Trolley Fire Extinguisher 50Kg Dry Powder Trolley

Trolley Fire Extinguisher, 50Kg Dry Powder ABC 40%, with 5m Discharge Hose and Valve with Pressure Gauge Safety Release Mechanism. 3rd Wheel added on the Front Side of the Fire Extinguisher Carriage for Easier Usage- Handling. Soft Material is used in the retaining wreaths of the vessel to avoid injuries and oxidation



CHARACTERISTICS

Approval Type	NF, BENOR, GTC, ITALY, MED, MIRTEC
Extinguisher Type	Trolley
Pressure Type	Stored Pressure
Suppression Agent Type	Powder
Capacity	50Kg
Extinguishing Agent	ABC 40%
Operating Temperature	-20 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	56 lt
Cylinder Height	900±3 mm
Cylinder Diameter	300±1 mm
Cylinder Neck Thread	G2"
Cylinder Material	DC01 (St12)
Valve Material	HPb59-1 (Nikel Plated)
Safety Valve	22-28 bar
Approx. gross Weight	85,5 kg
Approx. Dimensions	1200x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



BENOR

