

CODE: MBK14-500PA-EXT

ERP: 0135323

Trolley Fire Extinguisher 50Kg Dry Powder external cartridge Trolley

50Kg Trolley Fire Extinguisher with 5m Discharge Hose. The external cartridge contains Nitrogen (N₂) as propellant gas.

Soft Material is used in the retaining wreaths of the vessel to avoid injuries and oxidation

> SEPARATE CARRIAGE mounted on the Vessel



CHARACTERISTICS

Capacity	50Kg
Extinguishing Agent	ABC 40%
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	54 lt
Cylinder Height	880±6 mm
Cylinder Diameter	300±1 mm
Cylinder Neck Thread	G2"
Valve Material	HP295
Cylinder Material	HPb59-1
Safety Valve	22-27 bar
Approx. gross Weight	85,3 kg
Approx. Dimensions	1330x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



Issue Date: 20/06/2018

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: MAGOULA - ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiak.gr