

Fire Extinguisher 9Lt Foam with Int. Cartridge

Fire Extinguisher 9Lt Foam with Int. Cartridge Portable

Knob-Operated Fire Extinguisher 9Lt with one seam vessel with INTERNAL PLASTIC LAYER. Filled with environmentally friendly Foam.

METALLIC BRACKET INCLUDED

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS	
Approval Type	APRAGAZ, BENOR, MED, MIRTEC, NF, VKF
Extinguisher Type	Portable
Pressure Type	Cartridge
Suppression Agent Type	Foam
Capacity	9Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	11 lt
Cylinder Height	530±5 mm
Cylinder Diameter	180±1,5 mm
Cylinder Neck Thread	M74x2
Valve Material	AA6061-T6
Cylinder Material	DC01 (St12)
Safety Valve	21-26 bar
Approx. gross Weight	15,5 kg
Approx. Dimensions	655x230 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

