

Fire Extinguisher 6Lt Foam

Fire Extinguisher 6Lt Foam Portable

Fire Extinguisher 6Lt Foam 1,5%, with one seam vessel with Internal Plastic Layer and Pressure Gauge Safety Release Valve.

Metallic bracket included

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS	
Approval Type	ASSURALIA, BENOR, ITALY, KKI, MED, MIRTEC, NCP - KIWA, NF, TSE, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Foam
Capacity	6Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	7,9 lt
Cylinder Height	470±5 mm
Cylinder Diameter	160±1,5 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	10,5 kg
Approx. Dimensions	630x200 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

