

Fire Extinguisher 9Lt Foam

Fire Extinguisher 9Lt Foam Portable

Fire Extinguisher 9Lt with one seam vessel with INTERNAL PLASTIC LAYER and Pressure Gauge Safety Release Valve.

METALLIC BRACKET INCLUDED

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS	
Approval Type	BENOR, GTC, ITALY, MED, MIRTEC, NCP - KIWA, NF, TSE, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Foam
Capacity	9Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	11 lt
Cylinder Height	525±5 mm
Cylinder Diameter	180±1,5 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	18,74 kg
Approx. Dimensions	700x220 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

