

Fire Extinguisher 2kg CO2 EXCLUSIVE

Fire Extinguisher 2Kg CO2 EXCLUSIVE Portable

Fire Extinguisher 2Kg Carbon Dioxide with High Strength Front Outlet.

Height: 570mm

Galvanized bracket included

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	APRAGAZ, BENOR, CNBOP, GTC, ITALY, MED, MIRTEC, MPA DRESDEN, NCP - KIWA, NF, TSE, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	CO2
Capacity	2Kg
Extinguishing Agent	CO2
Operating Temperature	-20 to +60 °C
Max Allowable Pressure	174 bar
Test Pressure	250 bar
Volume of Equipment	3 lt
Cylinder Height	415±1,5 mm
Cylinder Diameter	114 ± 1,14 mm
Cylinder Neck Thread	25E
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	34CrMo4
Safety Valve	225±22,5 bar
Approx. gross Weight	6,5 kg
Approx. Dimensions	600 x 170 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

