

Fire Extinguisher 9 Lt with Ecological FluorFree Foam

Fire Extinguisher 9 Lt with Ecological FluorFree Foam Foam - Water

Fire Extinguisher 9Lt water with additive, with one seam vessel, Internal Plastic. Layer and Safety Release Valve.

100% Fluorine Free

METALLIC BRACKET INCLUDED

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	BENOR, MIRTEC, NCP - KIWA, NF, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Fluor Free, Water
Capacity	9
Extinguishing Agent	FFX150 premix
Operating Temperature	+5 ~+60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	11 lt
Cylinder Height	525±5 mm
Cylinder Diameter	180±1,5 mm
Cylinder Neck Thread	M30x1,5
Cylinder Material	DC01 (St12)
Valve Material	HPb59-1 (Nikel Plated)
Safety Valve	19-26 bar
Approx. gross Weight	18,74 kg
Approx. Dimensions	700x220 mm
Paint Finish	RAL 3000
Packaging Details	1 piece

