

Trolley Fire Extinguisher 10Kg CO2

Trolley Fire Extinguisher 10Kg CO2 Trolley

10Kg CO2 Trolley Fire Extinguisher with 16Lt Cylinder with 5m Discharge Hose.

HIGH-PRESSURE EPDM Discharge Hose of WP 155bar with Plastic Handle and Flow Control Valve, according to EN853 requirements, HEAVY Duty Carriage and wheels, Valve Protection HANDLE

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	MED, MIRTEC
Extinguisher Type	Trolley
Pressure Type	Stored Pressure
Suppression Agent Type	CO2
Capacity	10Kg
Extinguishing Agent	CO2
Operating Temperature	-20 to +60 °C
Max Allowable Pressure	174 bar
Test Pressure	300 bar
Volume of Equipment	16 lt
Cylinder Height	685±6,85 mm
Cylinder Diameter	200±2 mm
Cylinder Neck Thread	25E
Valve Material	DC01 (St12)
Cylinder Material	HPb59-1 (Nickel Plated)
Safety Valve	250-275 bar
Approx. gross Weight	63,8 kg
Approx. Dimensions	1100x400 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

EN1866



2010/35/EU (11)

EN1964