

## Fire Extinguisher 6Lt Foam with Int. Cartridge

### Fire Extinguisher 6Lt Foam with Int. Cartridge Portable

Knob-Operated Fire Extinguisher **6Lt** with one seam vessel with INTERNAL PLASTIC LAYER. Filled with environmentally friendly Foam.

METALLIC BRACKET INCLUDED

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



#### CHARACTERISTICS

|                        |                                      |
|------------------------|--------------------------------------|
| Approval Type          | APRAGAZ, BENOR, MED, MIRTEC, NF, VKF |
| Extinguisher Type      | Portable                             |
| Pressure Type          | Cartridge                            |
| Suppression Agent Type | Foam                                 |
| Capacity               | 6Lt                                  |
| Extinguishing Agent    | BSX233 1,5%                          |
| Operating Temperature  | +5 to +60 °C                         |
| Max Allowable Pressure | 18 bar                               |
| Test Pressure          | 27 bar                               |
| Volume of Equipment    | 7,75 lt                              |
| Cylinder Height        | 470±5 mm                             |
| Cylinder Diameter      | 160±1,5 mm                           |
| Cylinder Neck Thread   | M74x2                                |
| Valve Material         | AA6061-T6                            |
| Cylinder Material      | DC01 (St12)                          |
| Safety Valve           | 21-26 bar                            |
| Approx. gross Weight   | 11 kg                                |
| Approx. Dimensions     | 600x210 mm                           |
| Paint Finish           | RAL 3000                             |
| Packaging Details      | 1 pc.                                |

