

Fluorine Free Fire Extinguisher 6Lt with Int. Cartridge

Fluorine Free Fire Extinguisher 6Lt with Int. Cartridge Portable

Fire Extinguisher 6Lt water with additive, with internal CO2 cartridge, with one seam vessel, Internal Plastic Layer and Safety Release Valve.

100% Fluorine Free

METALLIC BRACKET INCLUDED*

*With optional Foam Cartridge During Activation and Discharge of the CO2 Internal Cartridge, the Foam is Released and Mixed with Water so that the Extinguisher is Ready for Use.



CHARACTERISTICS

Approval Type	BENOR, NF, VKF
Extinguisher Type	Portable
Pressure Type	Cartridge
Suppression Agent Type	Fluor Free
Capacity	6Lt
Extinguishing Agent	water with 1,5% additive A and 25% additive B
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	8 lt
Cylinder Height	470±5 mm
Cylinder Diameter	160±1.5 mm
Cylinder Neck Thread	M74x2
Valve Material	AA6061
Cylinder Material	St12 (DC01)
Safety Valve	21-26 bar
Approx. gross Weight	10.9 kg
Approx. Dimensions	570x180 mm
Paint Finish	RAL3000
Packaging Details	1pc

