

Trolley Fire Extinguisher 50lt Foam - NF

Trolley Fire Extinguisher 50Lt Foam - NF Trolley

Trolley Fire Extinguisher, 50Lt , with 5m Discharge Hose. Vessel with Internal Plastic layer. Valve with Gauge Safety Release Mechanism. 3rd Wheel added on the Front Side of the Fire Extinguisher Carriage for Easier Usage- Handling.

Soft Material is used in the retaining wreaths of the vessel to avoid injuries and oxidation



CHARACTERISTICS

Approval Type	BENOR, MIRTEC, NF
Extinguisher Type	Trolley
Pressure Type	Stored Pressure
Suppression Agent Type	Foam
Capacity	50Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	28 bar
Volume of Equipment	56,2±1 lt
Cylinder Height	900±10 mm
Cylinder Diameter	305±3 mm
Cylinder Neck Thread	G2"
Cylinder Material	HP295
Valve Material	HPb59-1 (Nikel Plated)
Safety Valve	22-28 bar
Approx. gross Weight	94,8 kg
Approx. Dimensions	1300x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



BENOR